

滑軸種類/SPOOL TYPES

02&03系列/SERIES

三位置/SPRING CENTERED 3 POSITIONS:

C 2 	C 3 	C 4 	C 5 	C 9
C 10 	C 11 	C 12 	C 60 	

二位置/ 2 POSITIONS:

B 2 	B 2L 	D 2 	D 8
B 3 	B 3L 	D 3 	

		D*-02			D*-03	
最大工作压力/ Max. operating pressure	P.A.B	7 MPa				
最大可能回油背压/ Max. permissible back pressure	T	7 MPa				
質量 / Mass	双電磁コイル Double solenoids	1.8	1.8	3.9	5	
	kg	1.42	1.42	3.35	3.9	
方向変換変率(回数/分)/ Changeover frequency(times/min)		240	120	240	120	240
操作温度範囲/Operating temperature range 5° c ~60° c						
操作粘度範囲/Operating viscosity 15~300cst						
濾す精度25µm或はもっと少ない Filtration 25µm or less						

電磁コイル/Solenoid coil		交流 AC				直流 DC			
						内蔵式整流/ Built-in rectifier			
電圧/Voltage(V)		AC110		AC220		AC110	AC220	DC12	DC24
頻率/Frequency(Hz)		50	60	50	60	50-60	50-60		
(02) 1/4"	起動電流/Starting current (A)	1.7	1.5	0.85	0.75	0.3	0.15	2.6	1.3
	維持電流/Holding current (A)	0.5	0.45	0.25	0.22				
維持電功率/Holding electric power(W)		18	21.5	18	21.5	25	25	31	31
(03) 3/8"	起動電流/Starting current (A)	3.7	3.2	1.8	1.6	0.36	0.2	2.75	1.5
	維持電流/Holding current (A)	0.75	0.65	0.37	0.32				
	維持電功率/Holding electric power(W)	27	33	27	33				
電圧可能範囲/Permissible voltage range (V)		100-120		200-240		100-120	200-240	10.8-13.2	21.6-26.4
絶縁抵抗/Insulation resistance (MΩ)		100或以上(500V)							